

SP	FC	IFI	CA	TIC	NC

SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-Nil Page 1 of 8 Date:20.05.2020

Name	Designation	Signature	Date	Level
Rohit Kumar	SSE / Design	Robert Ky	20.05.2020	Prepared
A.K. Agnihotri	SME / Design	A.	20.05.2020	Agreed
Kumar Sambhav	Dy. CME / Design	Sulm	20.05.2020	Reviewed
Mahesh Kumar	CDE	2 0000	20.05.2020	Approved

1. Introduction:

This specification covers technical and special requirements for developing State of the Art interiors for various LHB Sleeper coaches of Tejas Rake, to be manufactured by Modern Coach Factory of Indian Railways utilizing global expertise in the field of interior furnishing, materials/manufacturing technologies.

2. Scope of work:

S. No.	Item	Description & specification
i.	General	This covers the entire furnishing activity (both mechanical and
		electrical) to be done by contractor on AC HOT Buffet coaches.
		Firm shall take approval from MCF before bulk supply of items for
		executing the work. The contractor is expected to improve upon the
		drawings as per MCF to get best finish of the interiors and fitment,
		with due approval from CDE/MCF.
ii.	Contractor's	The interior furnishing (Supply and Apply Turnkey work) of the
	scope of work	coaches shall be carried out at MCF in shells allotted to them as
		per functional requirement of each variant as per scope of work
		and as mentioned in this specification.
		The term furnishing broadly includes the activities to be carried out
		in bare shells as mentioned in this specification and Purchase
		order.
		Prototype coach made by the firm with the design to be got
		approved by CDE/MCF









SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-NiI Page 2 of 8 Date:20.05.2020

iii.	Description and	This supply and apply furnishing turnkey work covers complete
	specifications	interior furnishing of AC Hot Buffet coaches for Tejas rake as per
		this specification. This specification is not exhaustive and overall
		responsibility to produce coaches with 6 years Warranty and
		upgraded interiors.
iv.	Contractor's	The contractor shall be entirely responsible for supply, Installation,
	responsibility	testing, commissioning and project supervision of the Furnishings and fittings for the coaches. The entire coach which includes the furnishing items under the scope of contractor shall be tested & commissioned at MCF.
		The contractor shall have MOU with OEMs/Manufacturers for items that are installed in coaches as per scope of work, in case these are bought out from any other firm and must submit the same before executing the work.
٧.	MCF's scope of	provide many crism than manage meeting mile to ore
	work	Rev-03, thermal insulation on inside roofs, sidewalls & under frame (wherever applicable), electrical wirings, air conditioning units and control panels, battery and EFT boxes. Exterior painting as per RDSO/2010/CG-08, Dust sealed gangway to spec no MMDTS 20034, Automatic body side entrance doors (Plug door) as per MDTS 25267 Rev-08, Bio Vacuum Evacuation system as per RDSO/2017/CG-06 Rev-03, Automatic Smoke/fire alarm system for passenger coaches as per RDSO/2008/CG-04 Rev-05 and Smart Coach Features shall be in scope of the MCF. The MCF shall also provide Bogie, Lowering & buffer height the coach on bogie, air brake system, draw gear and under gear equipment.









SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-NiI Page 3 of 8 Date:20.05.2020

3. Scope of work- AC Hot Buffet coach (LWCBAC)

The details of functional improvements and features which are to be incorporated in LHB AC-Hot Buffet coach for using it in improved Tejas Rake has been detailed below –

S.No	Features	Description 9 analification
i.	Layout drawing no.	Description & specification
ii.	•	LH90001 alt-nil
11.	General Installation	LH90004 alt-f: Existing drawings will be used along with
iii.	Coots and Doubles	upgraded features as mentioned in below paras
111.	Seats and Berths (Drg. no.	Ergonomic Seats and berths with improved cushioning, should
		be modular in design for all Seats & Berths with colour scheme
	MLH61001 alt-nil or latest)	as approved by CDE/MCF.
	or latest)	PU Foam Cushioning material as per specification MMDTS
		19020 Rev-03 Amnd-01and should be covered with a suitable
		Fire Barrier cloth to MMDTS 19021Rev-03.
iv.	Upper Berth	Upholstery should be as per MMDTS 19023 Rev-01.
IV.	Climbing	Climbing arrangement should be of AISI 304 buffed and Satin
	Arrangement	finished as per drawing no. MLH61100 alt-nil or latest. It has to
V.	Doors	be rugged enough to last up to coach life.
٧.	Doors	Existing drawing nos. LH56100 alt-j (except item no-3) should be used.
		[1] [1] [1] [1] [1] [1] [1] [1] [1] [1]
		(Main entrance doors will not be in this scope since automatic
vi.	Flooring	plug door will be in the scope of MCF)
vii.	Panelling &	Existing drawing no. LH41118 alt-nil should be used.
	Ceiling	Existing drawingno. LH44001 alt-d should be used.
viii.		The partition frame laminated panels (of saidly this)
	Partition Frames (Reference Drg. no. LH10001 alt-b)	The partition frame laminated panels (of existing thickness) should be LRTM or Vacuum bagging process (with the wooden pattern & colour scheme) sandwiched with Aluminium honeycomb as per MDTS 097 /Fire Retardant Composite Panel (FRCP) board (16 mm Thick as per specification MMDTS 20016) (Thickness 20 mm). Flange head rivet and socket head
		bolts to MMDTS18037 will be used in place of metallic inserts inside the honeycomb partition for fixing accessories i.e. magazine bag, bottle holder etc.
	NAC .	Bottle holder as per specification no. MMDTS 20020 shall be provided.
ix.	Windows/ Emergency Windows	Existing window arrangement as per drawing no. MLH54100 Alt-Nil or latest (except item no. 3) with Double Roller blinds as per specification MMDTS 20022.
x.	Luminaries and Lighting	Existing LED Lighting with Lux level as per RDSO specification no. RDSO/PE/SPEC/TL/0091-2016. All luminaries and lighting in entire coach including signages and Braille script should be as per LWACCN drawing.









SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-NiI Page 4 of 8 Date:20.05.2020

xi.	Charging point	Mobile Laptop charging point as per specification EDML-
		044,EDML-0043, EDML-0047.
xii.	Signages	Existing drawing (Drg.No. LH64100 alt-falt-nil) should be used.
xiii.	Sanitary facilities (Reference Drg. no. LH63001 Alt-d)	Lavatories should be of LRTM as per specification no. MMDTS 19044 or Vacuum bagging process as per specification no. MMDTS 20019. LRTM modular lavatory as per MMDTS 20021, with suitably sloped floor with Interior panels should be coated with anti graffiti coating as per RDSO Specification no. M&C/PCN/127-2009 with improved toilet seat mounting arrangement and all the amenities like mirror, foot operated water tap as per MMDTS 20031, soap dispenser for touch less experience and tissue paper dispenser as per MMDTS 20020. Attachment wall shall be provided as per drawing no. MLE64129 Alt'a' & MLE64130 Alt'a' shall be of LRTM as per specification no. MMDTS 19044 or Vacuum bagging process as per specification no. MMDTS 20019. Lavatory flooring pattern should be floor tiles type as per Specification No. MMDTS 20025 (2 mm thick) or EN45545 complied coating as per specification No. MMDTS 20018.
xiv.	Air Circulation System	Existing drawings (Drg. no. LH44101 alt-a) should be used.
xv.	Kitchen arrangement & equipments, Food storage arrangement	Modular integrated pantry units as per EDTS 118 Rev-e, amd1 Food storage arrangement should be as per drawing no LH64129 alt-nil
xvi.	Manager room arrangement and Lockers	Existing arrangement should be as per drawing nos LH64105 alt-b, LH61135 alt-c, LH44102 alt-a
xvii.	Marking diagram	Marking diagram as per drawing no. MLH83001 alt-nil or latest.
xviii.	Grips & level	LH24100 alt-b:Builder plate -Drg. No. MCF-LE64101 alt-nil
xix.	Layout of lettering inside (Braille script)	LH64100 alt-f: Furnishing plate-Drg. No.MCF-LE64102 alt-blntegrated Braille display / Braille stickers which shall be as per specification No. MMDTS 20024.

4. Important considerations:

i. Fire Smoke Toxicity Standards	All furnishing materials should comply the UIC 564-2 OR standards of fire retardant properties is as given below i.e.:
	 Resistance to spread of flame: Class A, as per UIC 564-2 OR Deterioration in visibility due to smoke: Class A,as per UIC 564-2 OR









SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-Nil Page 5 of 8 Date:20.05.2020

		 Limiting Oxygen Index: Minimum 35 as per UIC 564-2 OR (IS:13501) Toxicity: < 1 as per NCD-1409 (expect PU Foam)
ii.	Source	Firm should enable development of interior furnishing
	Development:	materials indigenously through MAKE IN INDIA effort to eliminate dependence on imports and ensure availability on priority.
iii.	Material to be applied	in the coaches should be environment friendly, non health
	hazards during applicat	ion and when disposed off as scrap.

5. Other Conditions:

S. No.	Item	Description & specification
i.	General	a) All tools and machineries required for the furnishing work
	conditions	shall be in the scope of contractor.
		b) All measuring instruments/ Gauges required for the subject work shall be in the scope of contractor.
		c) The contractor shall supply and install all items as per requirements specified in this scope of work.
		d) Normally the Shell will have the provision of back pieces as per standard arrangement. However, if there is any specific requirement by the contractor the same shall be met by the contractor himself and the same shall be provided with the approval of the CDE/MCF.
		e) It shall be noted that there may be minor variations in dimensions of the coach due to fabrication. The same shall be taken into consideration during furnishing work.
		f) During installation of all items under the scope of contractor, it shall be ensured that there is no resonant tendency in any of the sub assembly fitted by the contractor. All interior fittings should comply the functional requirements as mentioned in clauses of this specification. Sharp edges shall be avoided. All the interior fittings should have anti-pilferage feature.
		g) The composition and finish of all the materials covered under contractor's scope of supply shall meet respective specification requirements as covered in the relevant drawings/ specifications.
		h) The contractor shall execute any minor modifications/ improvements in design as suggested by competent authority without any financial implication. However, any modification required for meeting the functional objective shall necessarily be carried out.
		i) Coach interior dimensions such as furnishing thickness of









SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-NiI Page 6 of 8 Date:20.05.2020

		sidewall, partition, roof, end wall, gangway and toilets shall
		be strictly followed as per this specification.
		j) The movement of all the items under the scope of the
		contractor from depot/ feeder shop to assembly line will be
		contractor's responsibility.
ii.	Packing	All Components shall be packed in such a way so as to prevent
	instructions	any transit/ storage damages.
iii.	Receipt,	(a) The firm or their Authorized representative shall jointly
	installation &	inspect each of the consignment received at the MCF before
	fitment	unpacking is done and shall carry out a joint check of the
		receipt of components/ assemblies to avoid subsequent
		complaints regarding short receipt or transit damages. The
		joint check should be done within a fortnight of advice given
		by the MCF failing which the consignment shall be unpacked
		for installation at the risk of the firm in respect of shortage
		and damages.
		(b) The contractor shall depute adequate supervisors and staff
		for installation work.
		(c) All special tools, fixtures and other devices required for
		installation of fittings shall be provided by the firm and these
1.3		items shall become the property of the MCF/IR after
		completion of work.
iv.	Facilities to be	The Contractor shall be provided free of charge, the following
	provided by MCF to	facilities during the operation of the Contract by MCF near the site
	contractor:	of work:
		Power Supply, Compressed Air and water will be provided free of
		cost. However, the tenderer is advised to examine the actual site
		conditions for the last mile arrangements which is to be done by
		the firm for taking the compressed air and water from nearest
		tapping point (of compressed air and water) provided by Railways
		to the site and quote the rates, keeping in view these costs. All
		other facilities to be arranged by contractor himself.
		MCF shall provide adequate space inside covered shed (not
		enclosed) to the Contractor for keeping the material & tools required
		for day to day work. However, Contractor shall arrange the
		requisite lockers, cup boards, almirah etc of standard size for
		keeping the tools, materials, belongings etc. in safety in an orderly
		manner.
		MCF shall provide suitable crane for loading of Toilet modules. Fork
		lifters with driver for handling of materials free of cost.
v.	Inspection	Inspection of materials by MCF on WTC provided by the firmafter
		clearance of first prototype of each type of coaches. The
		furnishings and fittings supplied by the firm shall be supported by
		an inspection/ manufacturers test certificates from the supplier/
		contractors.









SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-NiI Page 7 of 8 Date:20.05.2020

vi.	Warranty	The furnishings and fittings supplied by the firm should be
	variancy	warranted for a period of 72 months from the date of installation at
vii.	Safety norms/	
vii.	Safety norms/ environmental management system norms to be followed by the contractor	the MCF for any customer complaint related to Design, Material and Manufacture. a) The contractor should take all precautionary measures in order to ensure the protection of his own personnel moving about or working on the MCF's premises, and should confirm to the rules and regulations of the MCF/IR. b) The contractor should abide by all MCF/IR regulations in force from time to time and ensure that the same are followed by his representative, agents or sub-contractors or workmen. c) The contractor should ensure that unauthorized, careless or inadvertent operation of installed equipment which may result in accident to staff and/or damage to equipment does not occur. d) The contractor should indemnify and keep the purchaser indemnified and harmless against all actions, suits, claims, demands, costs, charges or expenses arising in connection with any accident, death or injury, sustained by any person or persons within the MCF's premises and any loss or damage to Railway/MCF property sustained due to the Acts or omissions of the contractor irrespective of whether such liability arises under the workmen's compensation Act or the fatal accidents Act or any other statue in force from time to time. The Jurisdiction lies in the State of MCF. e) To ensure Human safety the contractor should use 24V hand lamp wherever lighting is not adequate inside the coach and Pneumatic drilling/Tapping machines should be used for coach wiring and other related works wherever required. f) The contractor shall ensure that all his workmen wear PPEs (Personal protection equipments) commensurate with the severity of work. g) The contractor shall ensure industrial safety methods in executing his work at the MCF. The contractor shall ensure that all wastes (includes cable bits, packing materials, wooden crates) generated during his activities/work both on coach as well as on the shop floor are segregated and moved to the respective dump sites or earmarked drums kept in shop floor on the day of then completion of the work. h) The contracto
		j) The contractor's staff shall be competent to operate
		emergency appliances like fire extinguishers.
		k) For any welding process carried out in the work, the Contractor shall certify that the Welders to be engaged shall possess minimum ITI qualification or have suitable experience









SCHEDULE OF TECHNICAL REQUIREMENT FOR SUPPLY, APPLY, INSTALLATION AND COMMISSIONING OF INTERIORS OF LHB AC HOT BUFFET COACHES FOR TEJAS RAKE.

MMDTS 20037 REV-Nil Page 8 of 8 Date:20.05.2020

		and sufficient working knowledge.
	1)	If on any day of work the number of workers employed by the
		Contractor is equal to or exceeds 20 (twenty) persons, the
		Contractor shall obtain Labour License from the Licensing
		Officer as per Contract Labour Act 1970 before
		commencement of the work and shall follow the latest
		guidelines as laid down by the Labour Commission rate, revised from time to time.
	m	The contractor shall comply with the latest provisions of the
2.52	111)	Factory Act, Employee's Compensation Act, contract labour
		Act, Employees Provident Fund and Miscellaneous Provisions
		Act or any other laws relating thereto and rules made from
		time to time and maintain relevant records.
	n)	The contractor shall have MOU with electrical contractor
		having valid electrical license and experience for executing all
		electrical works and proof of the same shall be submitted
		before executing the work. Certified Electrical fitters only shall
		be deputed for installation of electrical fittings/appliances and
		wiring connection.





